



Accessibility for wheelchair users

Walkway to the entrance: solid paved surface, 25 m from the parking lot to the entrance. Entrance building has three entrances: one main entrance with no differences in level, one entrance to the restaurant with a ramp, one entrance to the shop that has a concrete surface with level differences and a wooden ramp. The main entrance door has the width minimum of 84 cm and it is always open. The ramp to the restaurant has a slope of 11.7 %, handrails on one side and safety walls on the lefthand side.

Interior: ticket sales over a counter at the height of 110 cm; direct entrance from the parking lot. There is a restaurant in the entrance building and several small service points in the park. There is an exit from the restaurant to a terrace with level differences and steps. In the building there is a lift to the 2nd floor, equipped with an automatic door opener.

Park: walkways in the park are on fairly solid sandy surface.



Accessible for visually impaired

Walkway to the entrance: walkway is also used as a road for cars. The entrance building has three entrances: one main entrance with no differences in level, one entrance to the restaurant with a ramp, and one entrance to the shop that has a concrete floor with level differences.

Interior: ticket sales over a counter and with direct entrance from the parking lot. There is a restaurant in the entrance building and several small service points in the park. There is an exit from the restaurant to a terrace with level differences and steps.

Park: walkways in the park are on fairly solid sandy surface.



Disabled parking

A designated and paved disabled parking space on the same side as the park, 25 m from the entrance. The main parking lot on the other side of the road is reached through a pedestrian tunnel with a slope of 20 %.



Accessible for persons with asthma and allergies

No animals are allowed inside the premises.

Toilets, including disabled toilets, are situated in a separate building near the entrance. A ramp to the door has a slope of 9.43 %.



Disabled toilet

- size 160x160 cm
- door width 80 cm
- toilet seat minimum 44 cm
- support handle on both sides
- one-handle mixer
- door can be locked from the inside with one hand



Accessible lift

- size 125x340 cm
 - contrasting-coloured lift door with the width of 85 cm
 - toilet seat height minimum of 41 cm
 - automatic slide-door or automatic door opening
 - operator panel in the lift at the height of 80 cm and 70 cm from the corner
 - buttons on operator panel have relief and tactile symbols
 - handrail on longside of the lift
 - acoustic alarm
 - emergency phone and alarm have tactile and visual markings
-